

Product Code: CMA032

Description: 13A 2 Gang Unswitched Socket Outlet



General Information

Plate Dimensions (mm)	146 (W) x 86 (H) x 9.5 (D)
Plate Fixing Centres - Horizontal (mm)	120.6
Style	Rounded Profile
Finish	Polar White
Materials	Front Plate: Urea Terminals: Brass Earth Strap: Mild Steel
Anti Microbial Certified	Yes
Rated Voltage (V~) (Ue)	250
Resistive Load Rating (A)	13
Termination Type	Screw
Terminal Size (mm)	Ø5
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4
Switched	No
Twin Earth Terminals	Yes
Minimum Back Box Depth (mm)	25
Ingress Protection	IP20
Operational Temperature (°C)	-5 to +40
Warranty (Years)	20

Rear Housing: Urea
Terminal Screws: Steel & Yellow Passivated

Frequency (Hz) 50

Terminal Torque Value (Nm) 2

Standards BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.
All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.