

Technical Specification

Product Code: VPCH204WH Description: 45A 2 Gang Double Pole Switch With 13A Double Pole Switched Socket





Insert, Switch & Rear Housing: Urea

Gasket: Nylon

Terminal Torque Value (Nm) 2.5

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

General Information

Plate Dimensions (mm) 146 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 149 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm)

Style Victorian

Finish Polished Chrome

White Insert Colour Gasket Colour White

> Materials Front Plate: Stainless Steel

> > Terminals: Brass Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Anti Microbial Certified No Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50

Resistive Load Rating (A) 45 Termination Type Screw

Terminal Size (mm) 016

Terminal Capacity - Solid (mm²) 1 x 16

Double Pole Switch Yes Twin Earth Terminals

Product Marking Cooker

Minimum Back Box Depth (mm) 35

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

> Warranty (Years) 10

Standards BS 4177

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

