

Product Code: MM030WH

Description: 15A 110V US Socket Outlet Module



General Information

Dimensions (mm)	50 (W) x 50 (H) x 25.5 (D)	
Finish	Polar White	
Materials	Cover & Housing: Polycarbonate	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated	Internal Busbars: Formed Pressed Brass
Anti Microbial Certified	No	
Rated Voltage (V~) (Ue)	125	Frequency (Hz)
Resistive Load Rating (A)	15	
Termination Type	Screw	
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4	
Minimum Back Box Depth (mm)	25 (35 Flat Plate)	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	1	

Standards UL 498

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 The US module requires a 125V 60Hz supply for use with US appliance plugs
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.