

Technical Specification

Product Code: VPSC038BK **Description:** 5A Round Pin Socket Outlet





General Information

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D) Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Victorian Finish Satin Chrome

Insert Colour Black Gasket Colour Black

Materials Front Plate: Stainless Steel Insert: Urea Rear Housing: Nylon Terminals: Brass

Terminal Screws: Steel & Yellow Passivated

Earth Strap: Mild Steel

Internal Busbars: Formed Pressed Brass

Gasket: Nylon

Terminal Torque Value (Nm)

Anti Microbial Certified

Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50

Resistive Load Rating (A) Termination Type Screw Terminal Size (mm)

Terminal Capacity - Solid (mm²) 4 x 1.5 or 3 x 2.5

Switched No.

Twin Earth Terminals No Minimum Back Box Depth (mm) 25

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS 546

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

