

Product Code: VPSC066BK

Description: Twin Non-Isolated Coaxial Outlet



General Information

Plate Dimensions (mm)	88 (W) x 88 (H) x 8 (D)
Dimensions With Gasket (mm)	91 (W) x 91 (H) x 9 (D)
Plate Fixing Centres - Horizontal (mm)	60.3
Style	Victorian
Finish	Satin Chrome
Insert Colour	Black
Gasket Colour	Black
Materials	Front Plate: Stainless Steel Terminals: Brass Gasket: Nylon
Anti Microbial Certified	No
Termination Type	Screw
Isolated	No
Non-Isolated	Yes
Non-Isolated Comments	Enables 2 way signal transmission
Shielded	No
Minimum Back Box Depth (mm)	16
Ingress Protection	IP20
Operational Temperature (°C)	-5 to +40
Warranty (Years)	10

Insert: Urea
Earth Plate: Mild Steel

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Isolated socket will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.