

## **Technical Specification**

CLICK

• • • • • ScolmoreGROUP

Product Code: VPSC204WH Description: 45A 2 Gang Double Pole Switch With 13A Double Pole Switched Socket

Outlet





Insert, Switch & Rear Housing: Urea

Gasket: Nylon

Terminal Torque Value (Nm) 2.5

Frequency (Hz) 50

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

## **General Information**

Plate Dimensions (mm) 146 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm)  $149 (W) \times 91 (H) \times 9 (D)$ 

Plate Fixing Centres - Horizontal (mm) 120.6

Style Victorian
Finish Satin Chrome

Insert Colour White Gasket Colour White

Materials Front Plate: Stainless Steel

Terminals: Brass Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Anti Microbial Certified No

Rated Voltage (V~) (Ue) 250

Resistive Load Rating (A) 45
Termination Type Screw

Terminal Size (mm) Ø6

Terminal Capacity - Solid (mm²) 1 x 16

Double Pole Switch Yes

Twin Earth Terminals Yes
Product Marking Cooker

Minimum Back Box Depth (mm) 35

William Back Box Deptil (IIIII)

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS 4177

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

