

Technical Specification

CLICK® Scolmoregroup

Product Code: FPSS722WH Description: 20A Ingot Double Pole Plate Switch





Insert & Housing: Urea

Earth Strap: Mild Steel

Frequency (Hz) 50

Contacts: Silver "on-lay" Copper / Brass

Terminals: Brass

Terminal Torque Value (Nm)

General Information

Plate Dimensions (mm) 86 (W) \times 86 (H) \times 1.3 (D) Dimensions With Gasket (mm) 86 (W) \times 86 (H) \times 3 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

Style Flat Plate
Finish Stainless Steel

Insert Colour White

Gasket Colour Transparent (Neoprene)

Materials Front Plate: Stainless Steel

Switch Cover: Stainless Steel
Terminal Screws: Steel & Yellow Passivated

Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass

Anti Microbial Certified No

Rated Voltage (V~) (Ue) 250

Resistive Load Rating (A) 20
Termination Type Screw
Terminal Size (mm) Ø5

Terminal Capacity - Solid (mm²) 3 x 2.5

Double Pole Switch Yes
Twin Earth Terminals Yes

Minimum Back Box Depth (mm) 35 Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS EN 60669-1

Additional Information For

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

