

Product Code: FS030SS

Description: 13A 1 Gang Floor Socket Outlet



General Information

Dimensions (mm)	86 (W) x 93 (D) x 5 (H)	
Plate Fixing Centres - Horizontal (mm)	60.3	
Finish	Stainless Steel	
Materials	Plate & Lid: Stainless Steel	Insert: Urea
	Internal Busbars: Brass	Terminals: Brass
	Terminal Screws: Steel and Yellow Passivated	Earth Bar: Mild Steel
Anti Microbial Certified	No	
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Termination Type	Screw	
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm) 2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4	
Switched	No	
Twin Earth Terminals	No	
Minimum Back Box Depth (mm)	35	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	
Standards	BS 1363-2	

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.