

Product Code: FPBN535BK

Description: 13A Ingot 1 Gang Double Pole Switched Socket Outlet



General Information

Plate Dimensions (mm)	86 (W) x 86 (H) x 1.3 (D)	
Dimensions With Gasket (mm)	86 (W) x 86 (H) x 3 (D)	
Plate Fixing Centres - Horizontal (mm)	60.3	
Style	Flat Plate	
Finish	Black Nickel	
Insert Colour	Black	
Gasket Colour	Transparent (Neoprene)	
Materials	Front Plate: Stainless Steel Switch Cover: Stainless Steel Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass	Insert & Housing: Urea Terminals: Brass Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel
Anti Microbial Certified	No	
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Termination Type	Screw	
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm) 2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4	
Double Pole Switch	Yes	
Minimum Back Box Depth (mm)	35	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

Standards BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.