





Technical Specification

Product Code: FPBS426BK Description: 2 Gang MiniGrid® Unfurnished Plate - 6 In-Line Apertures





General Information

 $\begin{array}{ccc} \textbf{Plate Dimensions (mm)} & 146 \text{ (W)} \times 88 \text{ (H)} \times 1.3 \text{ (D)} \\ \textbf{Dimensions With Gasket (mm)} & 146 \text{ (W)} \times 88 \text{ (H)} \times 3 \text{ (D)} \\ \end{array}$

Plate Fixing Centres - Horizontal (mm) 120.6

MiniGrid Plate (Gang) 2

MiniGrid Single Width Module Quantity 6
MiniGrid Double Width Module Quantity 3

Style Flat Plate

Finish Brushed Stainless

Insert Colour Black

Gasket Colour Transparent (Neoprene)

Materials Front Plate: Stainless Steel

Terminals: Brass

Earth Strap: Mild Steel

Anti Microbial Certified No

Termination Type Screw

Modular Rocker Switches Yes

Minimum Back Box Depth (mm) Dependent On Modules Fitted

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS 5733

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Interchangeable with modules in the MiniGrid Range.

MINIGRID®

Insert: Urea

Terminal Screws: Steel & Yellow Passivated

