

Product Code: VPSB651BK

Description: 13A Double Pole Switched Fused Connection Unit



## General Information

Plate Dimensions (mm)	88 (W) x 88 (H) x 8 (D)	Insert, Switch, Fuse Drawer & Housing: Urea
Dimensions With Gasket (mm)	91 (W) x 91 (H) x 9 (D)	Terminal Screws: Steel & Yellow Passivated
Plate Fixing Centres - Horizontal (mm)	60.3	Internal Busbars: Formed Pressed Brass
Style	Victorian	Gasket: Nylon
Finish	Satin Brass	
Insert Colour	Black	
Gasket Colour	Black	
Materials	Front Plate: Stainless Steel Terminals: Brass Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel	
Anti Microbial Certified	No	
Rated Voltage (V~) (Ue)	250	
Resistive Load Rating (A)	13	
Fuse Fitted Rating & Type	13A (BS 1362)	
Termination Type	Screw	
Terminal Size (mm)	Ø5	Frequency (Hz) 50
Terminal Capacity - Solid (mm <sup>2</sup> )	3 x 2.5 or 2 x 4	Terminal Torque Value (Nm) 2
Switched	Yes	
Double Pole Switch	Yes	
Twin Earth Terminals	Yes	
Product Marking	Fused	
Minimum Back Box Depth (mm)	25	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	
Standards	BS 1363-4 BS 1362	

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.