

Product Code: PA380WH**Description:** 13A Resilient Non-Standard Plug Top (13A Fused) Bar Grip

General Information

Dimensions (mm)	49.5 (W) x 21 (D) x 49.5 (H)	
Finish	White	
Materials	Body: Nylon Internal Busbars: Formed Pressed Brass	Pins: Brass Fuse: BS 1362 Approved
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Fuse Fitted Rating & Type	13A (BS 1362)	
Termination Type	Screw	
Terminal Size (mm)	Ø3.1	Terminal Torque Value (Nm) 0.4
Terminal Capacity - Solid (mm²)	1.5	
Product Marking	Fused	
Cable Entry Dimensions (mm)	Ø10.8	
Cable Restraint Supplied	Yes	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	
Standards	BS 1363/A BS 1362	

Additional Information	For cleaning / polishing of products, use only a soft, dry, clean cloth. Always refer to the circuit diagram supplied with the relevant product. The non-standard plugs are suitable for use only with the non-standard sockets, product codes CMA935 and CMA936.
-------------------------------	---