

Product Code: PRC216

Description: 16A Double Pole Pull Cord Switch With Neon



General Information

Dimensions (mm)	70 (Dia) x 42 (D)	Style	Round
Finish	Polar White	Materials	Cover & Pattress: Urea Neon Lens: Polycarbonate Terminal Screws: Steel & Yellow Passivated Earth Strap: Mild Steel
Anti Microbial Certified	Yes	Terminal Housing	Urea
Rated Voltage (V~) (Ue)	250	Terminals	Brass
Resistive Load Rating (A)	16	Internal Busbars	Formed Pressed Brass
Termination Type	Screw	Pull Bell	Urea
Terminal Size (mm)	Ø4	Frequency (Hz)	50
Terminal Capacity - Solid (mm ²)	2 x 1.5 or 1 x 2.5	Terminal Torque Value (Nm)	0.4
Double Pole Switch	Yes	Indicator Colour	Orange
Twin Earth Terminals	No	Back Box Knockouts - Sides (mm)	2 x 18 x 6.5
Neon Indicator	Yes	Back Box Knockouts - Rear (mm)	2 x 18 x 8
Supplied Back Box Depth (mm)	Pattress Supplied		
Back Box Knockouts - Total (mm)	2 x 18 x 6.5 and 2 x 18 x 8		
Back Box Knockouts - Top (mm)	None		
Back Box Knockouts - Bottom (mm)	None		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.