

Technical Specification

Product Code: MD022CH

Description: 20A Ingot Double Pole Switch Module



General Information

| | | |
|--|--|---|
| Dimensions (mm) | 41 (W) x 52.5 (H) x 22 (D) | |
| Finish | Polished Chrome | |
| Materials | Rocker Switch: Urea Switch Cover: Stainless Steel Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass | Rear Housing: Nylon Terminals: Brass Contacts: Silver "on-lay" Copper / Brass |
| Rated Voltage (V~) (Ue) | 250 | Frequency (Hz) 50 |
| Resistive Load Rating (A) | 20 | |
| Termination Type | Screw | |
| Terminal Size (mm) | Ø4.4 | Terminal Torque Value (Nm) 1.2 |
| Terminal Capacity - Solid (mm ²) | 3 x 2.5 or 2 x 4 | |
| Modular Rocker Switches | Yes | |
| Double Pole Switch | Yes | |
| Minimum Back Box Depth (mm) | 25 (35 Flat Plate) | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 10 | |

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.