

Technical Specification



Product Code: VPCH536WH Description: 13A Ingot 2 Gang Double Pole Switched Socket Outlet





Insert & Housing: Urea

Earth Strap: Mild Steel

Frequency (Hz) 50

Contacts: Silver "on-lay" Copper / Brass

Terminals: Brass

Terminal Torque Value (Nm) 2

General Information

Plate Dimensions (mm) 146 (W) \times 88 (H) \times 8 (D) Dimensions With Gasket (mm) 149 (W) \times 91 (H) \times 9 (D)

Plate Fixing Centres - Horizontal (mm) 120.6

Style Victorian

Finish Polished Chrome

Insert Colour White Gasket Colour White

Materials Front Plate: Stainless Steel

Switch Cover: Stainless Steel

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Gasket: Nylon

Anti Microbial Certified No

Rated Voltage (V~) (Ue) 250

Resistive Load Rating (A) 13

Termination Type Screw **Terminal Size (mm)** Ø5

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Double Pole Switch Yes
Twin Earth Terminals Yes

Minimum Back Box Depth (mm) 25

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS 1363-2

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

