

Product Code: MD029BN

Description: 10AX Ingot Double Pole Keyswitch Module



General Information

Dimensions (mm)	25 (W) x 52.5 (H) x 20 (D)	
Finish	Black Nickel	
Materials	Cover & Rocker Switch: Urea Cover: Stainless Steel Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass	Rear Housing: Nylon Terminals: Brass Contacts: Silver "on-lay" Copper / Brass
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Inductive Load Rating (AX)	10	
Load Rating Comments	Suitable for Inductive Loads	
Termination Type	Screw	
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm) 0.5
Terminal Capacity - Solid (mm²)	4 x 1.5 or 2 x 2.5	
Modular Rocker Switches	Yes	
Double Pole Switch	Yes	
Keyswitch	Yes	
Product Marking	Emergency Test	
Minimum Back Box Depth (mm)	16 (25 Flat Plate)	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.