

Technical Specification

CLICK® Scolmoregroup

Product Code: MD047BKSC Description: 13A Ingot Fused Connection Module





Rear Housing: Nylon

Frequency (Hz) 50

Internal Busbars: Formed Pressed Brass

Terminals: Brass

Terminal Torque Value (Nm) 0.5

General Information

 $\textbf{Dimensions (mm)} \quad 25 \text{ (W)} \times 57 \text{ (H)} \times 25.2 \text{ (D)}$

Finish Satin Chrome

Insert Colour Black

Materials Cover & Fuse Drawer: Nylon

Drawer Cover: Stainless Steel

Terminal Screws: Steel & Yellow Passivated

Rated Voltage (V~) (Ue) 250

Resistive Load Rating (A) 13

Fuse Fitted Rating & Type 13A (BS 1362)

Termination Type Screw

Terminal Size (mm) Ø3.5

Terminal Capacity - Solid (mm²) 4 x 1.5 or 2 x 2.5

Modular Rocker Switches Yes

Product Marking Fused Symbol

Minimum Back Box Depth (mm) 25 (35 Flat Plate)

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS 5733

BS 1362

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

