

Product Code: MD047BKSS

Description: 13A Ingot Fused Connection Module



General Information

Dimensions (mm)	25 (W) x 57 (H) x 25.2 (D)	
Finish	Stainless Steel	
Insert Colour	Black	
Materials	Cover & Fuse Drawer: Nylon Drawer Cover: Stainless Steel Terminal Screws: Steel & Yellow Passivated	Rear Housing: Nylon Terminals: Brass Internal Busbars: Formed Pressed Brass
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Fuse Fitted Rating & Type	13A (BS 1362)	
Termination Type	Screw	
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm) 0.5
Terminal Capacity - Solid (mm ²)	4 x 1.5 or 2 x 2.5	
Modular Rocker Switches	Yes	
Product Marking	Fused Symbol	
Minimum Back Box Depth (mm)	25 (35 Flat Plate)	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	
Standards	BS 5733 BS 1362	

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.