

**Product Code:** MD047WHSC

**Description:** 13A Ingot Fused Connection Module



## General Information

|                                        |                                                                                                           |                                                                                   |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
| <b>Dimensions (mm)</b>                 | 25 (W) x 57 (H) x 25.2 (D)                                                                                |                                                                                   |
| <b>Finish</b>                          | Satin Chrome                                                                                              |                                                                                   |
| <b>Insert Colour</b>                   | Click White                                                                                               |                                                                                   |
| <b>Materials</b>                       | Cover & Fuse Drawer: Nylon<br>Drawer Cover: Stainless Steel<br>Terminal Screws: Steel & Yellow Passivated | Rear Housing: Nylon<br>Terminals: Brass<br>Internal Busbars: Formed Pressed Brass |
| <b>Rated Voltage (V~) (Ue)</b>         | 250                                                                                                       | <b>Frequency (Hz)</b> 50                                                          |
| <b>Resistive Load Rating (A)</b>       | 13                                                                                                        |                                                                                   |
| <b>Fuse Fitted Rating &amp; Type</b>   | 13A (BS 1362)                                                                                             |                                                                                   |
| <b>Termination Type</b>                | Screw                                                                                                     |                                                                                   |
| <b>Terminal Size (mm)</b>              | Ø3.5                                                                                                      | <b>Terminal Torque Value (Nm)</b> 0.5                                             |
| <b>Terminal Capacity - Solid (mm²)</b> | 4 x 1.5 or 2 x 2.5                                                                                        |                                                                                   |
| <b>Modular Rocker Switches</b>         | Yes                                                                                                       |                                                                                   |
| <b>Product Marking</b>                 | Fused Symbol                                                                                              |                                                                                   |
| <b>Minimum Back Box Depth (mm)</b>     | 25 (35 Flat Plate)                                                                                        |                                                                                   |
| <b>Operational Temperature (°C)</b>    | -5 to +40                                                                                                 |                                                                                   |
| <b>Warranty (Years)</b>                | 10                                                                                                        |                                                                                   |
| <b>Standards</b>                       | BS 5733<br>BS 1362                                                                                        |                                                                                   |

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.