

Product Code: MD070PN

Description: 10A Ingot 3 Position Switch Module



General Information

Dimensions (mm)	25 (W) x 57 (H) x 27 (D)	
Finish	Pearl Nickel	
Materials	Rocker Switch: Urea Switch Cover: Stainless Steel Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass	Rear Housing: Nylon Terminals: Brass Contacts: Silver "on-lay" Copper / Brass
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	10	
Termination Type	Screw	
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm) 0.5
Terminal Capacity - Solid (mm²)	4 x 1.5 or 2 x 2.5	
Modular Rocker Switches	Yes	
1 Pole 3 Position Switch	Yes	
Minimum Back Box Depth (mm)	25 (35 Flat Plate)	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.