

Technical Specification



Product Code: VPSS752WH Description: 13A Ingot Double Pole Switched Fused Connection Unit With Neon





General Information

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Victorian Finish Stainless Steel

> > 250

Insert Colour White Gasket Colour White

Materials Front Plate: Stainless Steel

Switch & Fuse Drawer Cover: Stainless Steel

Terminals: Brass Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Frequency (Hz) 50

Insert & Housing: Urea

Neon Lens: Polycarbonate

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Rated Voltage (V~) (Ue) Resistive Load Rating (A) 13

Anti Microbial Certified

Fuse Fitted Rating & Type 13A (BS 1362)

> Termination Type Screw

Terminal Size (mm) Terminal Torque Value (Nm) 2 05

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

> Switched Yes

Double Pole Switch Yes Twin Earth Terminals Yes

> Neon Indicator Yes Indicator Colour Red

Product Marking Fused

Minimum Back Box Depth (mm) Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS 1363-4

BS 1362

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

