

Product Code: MD017WHBS

Description: 20A Ingot Flex Outlet Module



General Information

Dimensions (mm)	25 (W) x 56.5 (H) x 30 (D)	
Finish	Brushed Stainless	
Insert Colour	Click White	
Materials	Blank: Urea	
	Cover: Stainless Steel	
	Terminal Screws: Steel & Yellow Passivated	
	Cord Grip: Nylon	
	Rear Housing: Nylon	
	Terminals: Brass	
	Bracket: Mild Steel	
	Screws: Nickel Plated Steel	
Rated Voltage (V~) (Ue)	250	
Resistive Load Rating (A)	20	
Termination Type	Screw	
Terminal Size (mm)	Ø3.5	
Terminal Capacity - Solid (mm²)	4 x 1.5 or 2 x 2.5	
Modular Rocker Switches	Yes	
Flex Outlet Available	Yes	
Flex Outlet Location	Front of Plate	
Minimum Back Box Depth (mm)	25 (35 Flat Plate)	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	
	Frequency (Hz)	50
	Terminal Torque Value (Nm)	0.5
	Flex Outlet Dimension (mm)	Ø10

Standards BS 5733

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.