

## Technical Specification

Product Code: MD017WHSC

Description: 20A Ingot Flex Outlet Module



### General Information

Dimensions (mm)	25 (W) x 56.5 (H) x 30 (D)	
Finish	Satin Chrome	
Insert Colour	Click White	
Materials	Blank: Urea Cover: Stainless Steel Terminal Screws: Steel & Yellow Passivated Cord Grip: Nylon	Rear Housing: Nylon Terminals: Brass Bracket: Mild Steel Screws: Nickel Plated Steel
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	20	
Termination Type	Screw	
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm) 0.5
Terminal Capacity - Solid (mm <sup>2</sup> )	4 x 1.5 or 2 x 2.5	
Modular Rocker Switches	Yes	
Flex Outlet Available	Yes	
Flex Outlet Location	Front of Plate	Flex Outlet Dimension (mm) Ø10
Minimum Back Box Depth (mm)	25 (35 Flat Plate)	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	
Standards	BS 5733	

### Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.