

Product Code: SIN204BK

Technical Specification

Description: 45A 2 Gang Double Pole Switch With 13A Double Pole Switched Socket

Outlet Insert





General Information

Insert Dimensions (mm) $142.5 (W) \times 82.5 (H) \times 2.5 (D)$

Plate Fixing Centres - Horizontal (mm) 120.6

Style Screwless Insert

Insert Colour Black
Compatible Cover Plate SCP204#

Jover Plate 30F204#

Materials Insert: Polycarbonate Switch & Rear Housing: Urea

Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Anti Microbial Certified No

Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50

Resistive Load Rating (A) 45
Termination Type Screw

Terminal Size (mm) Ø6 Terminal Torque Value (Nm) 2.5

Terminal Capacity - Solid (mm²) 1 x 16

Double Pole Switch Yes
Twin Earth Terminals Yes

Product Marking Cooker

Minimum Back Box Depth (mm) 47

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS 4177

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.





Technical Specification



Product Code: SCP204** Description: 1 Gang GridPro® Frontplate


General Information

Dimensions (mm) 146 (W) x 86 (H) x 4 (D)


Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), MB (Metal Black), MW (Metal

White), BK (Matt Black) & PW (Polar White)

Plate Materials Decorative & Metal Black or White: Stainless Steel, Black & Polar White: Polycarbonate









SCP204BS

SCP204CH

SCP204SS








SCP204MB

SCP204MW

SCP204BK



SCP204PW