

Product Code: SIN650BK

## **Technical Specification**

**Description:** 13A Fused Connection Unit Insert





Internal Busbars: Formed Pressed Brass

## **General Information**

Insert Dimensions (mm) 82.5 (W) x 82.5 (H) x 2.5 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Screwless Insert

Insert Colour Black Compatible Cover Plate SCP250#

> Materials Insert: Polycarbonate

Rear Housing: Urea Rear Housing: Urea Terminals: Brass

Terminal Screws: Steel & Yellow Passivated

Earth Strap: Mild Steel

Anti Microbial Certified Rated Voltage (V~) (Ue) 250 Frequency (Hz)

Resistive Load Rating (A) 13 Termination Type Screw

> Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 2

Terminal Capacity - Solid (mm<sup>2</sup>) 3 x 2.5 or 2 x 4

Switched

Twin Earth Terminals Yes

Minimum Back Box Depth (mm)

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS 1363-4

BS 1362

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.







## **Technical Specification**



Product Code: SCP250\*\*

Description: 13A Fused Connection Unit Cover Plate

## **General Information**

**Dimensions (mm)** 86 (W) x 86 (H) x 4 (D)

Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), MB (Metal Black), MW (Metal

White), BK (Matt Black) & PW (Polar White)

Plate Materials Decorative & Metal Black or White: Stainless Steel, Black & Polar White: Polycarbonate



SCP250BS



SCP250CH



SCP250SS



SCP250MB



SCP250MW



SCP250BK



SCP250PW