

Product Code: SIN651PW

Technical Specification

Description: 13A Double Pole Switched Fused Connection Unit Insert





Rear Housing: Urea

Earth Strap: Mild Steel

Frequency (Hz) 50

Contacts: Silver "on-lay" Copper / Brass

Terminals: Brass

Terminal Torque Value (Nm) 2

General Information

Insert Dimensions (mm) 82.5 (W) x 82.5 (H) x 2.5 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

Style Screwless Insert Insert Colour Polar White

Compatible Cover Plate SCP251#

Materials Insert : Polycarbonate

Rear Housing: Urea

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Anti Microbial Certified No Rated Voltage (V~) (Ue) 250

Resistive Load Rating (A) 13

Termination Type Screw

Terminal Size (mm) Ø5

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Switched Yes

Double Pole Switch Yes

Twin Earth Terminals Yes

Minimum Back Box Depth (mm) 35

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS 1363-4

BS 1362

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.





Technical Specification



Product Code: SCP251**

Description: 13A Switched Fused Connection Unit Cover Plate


General Information

Dimensions (mm) 86 (W) x 86 (H) x 4 (D)

Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), MB (Metal Black), MW (Metal

White), BK (Matt Black) & PW (Polar White)

Plate Materials Decorative & Metal Black or White: Stainless Steel, Black & Polar White: Polycarbonate



SCP251BS




SCP251CH



SCP251SS



SCP251MB



SCP251MW



SCP251BK

