

Product Code: SIN035BK

Technical Specification

Description: 13A 1 Gang Double Pole Switched Socket Outlet Insert





General Information

Insert Dimensions (mm) 82.5 (W) x 82.5 (H) x 2.5 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Screwless Insert

Insert Colour Black Compatible Cover Plate SCP435#

> Materials Insert: Polycarbonate Rear Housing: Urea

> > Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Anti Microbial Certified

Rated Voltage (V~) (Ue) 250 Frequency (Hz)

Resistive Load Rating (A) 13 Termination Type Screw

> Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 2

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

> Double Pole Switch Twin Earth Terminals

Minimum Back Box Depth (mm) 35

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.







Technical Specification



Product Code: SCP435**

Description: 13A 1 Gang Switched Socket Outlet Cover Plate

General Information

Dimensions (mm) 86 (W) x 86 (H) x 4 (D)


Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), MB (Metal Black), MW (Metal

White), BK (Matt Black) & PW (Polar White)

Plate Materials Decorative & Metal Black or White: Stainless Steel, Black & Polar White: Polycarbonate



SCP435BS




SCP435CH




SCP435SS




SCP435MB



SCP435MW



SCP435BK



SCP435PW