

Technical Specification

Product Code: SIN036PW **Description:** 13A 2 Gang Double Pole Switched Socket Outlet Insert





General Information

Insert Dimensions (mm) 142.5 (W) x 82.5 (H) x 2.5 (D)

Plate Fixing Centres - Horizontal (mm) 120.6

> Style Screwless Insert

Insert Colour Polar White Compatible Cover Plate SCP436#

> Materials Insert: Polycarbonate

Rear Housing: Urea

Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Anti Microbial Certified

Rated Voltage (V~) (Ue) 250 Frequency (Hz)

Resistive Load Rating (A) 13 Termination Type Screw

> Terminal Size (mm) Terminal Torque Value (Nm) 2 Ø5

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

> Double Pole Switch Twin Earth Terminals Yes

Minimum Back Box Depth (mm) 35

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.





Technical Specification



Product Code: SCP436**

Description: 13A 2 Gang Switched Socket Outlet Cover Plate


General Information

Dimensions (mm) 146 (W) x 86 (H) x 4 (D)


Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), MB (Metal Black), MW (Metal

White), BK (Matt Black), PW (Polar White) & RD (Red)


Plate Materials Decorative & Metal Black or White: Stainless Steel, Black, Polar White & Red: Polycarbonate










SCP436BS SCP436CH SCP436SS








SCP436MB SCP436MW SCP436BK





SCP436PW SCP436RD

UK Design Registration: 3015621