

Product Code: SIN038BK

## **Technical Specification**

**Description:** 5A Round Pin Socket Outlet Insert





## **General Information**

**Insert Dimensions (mm)** 82.5 (W) x 82.5 (H) x 2.5 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

Style Screwless Insert

Insert Colour Black
Compatible Cover Plate SCP238#

Materials Insert: Polycarbonate Rear Housing: Nylon

Terminals: Brass Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel

Anti Microbial Certified No

Rated Voltage (V~) (Ue) 250

Frequency (Hz) 50

Resistive Load Rating (A) 5
Termination Type Screw

Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 1.2

Terminal Capacity - Solid (mm²)  $4 \times 1.5$  or  $3 \times 2.5$ 

Switched No

Twin Earth Terminals No

Minimum Back Box Depth (mm) 35

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS 546

**Additional Information** For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.





## **Technical Specification**



Product Code: SCP238\*\*

Description: 5A Round Pin Socket Outlet Cover Plate

## **General Information**

**Dimensions (mm)** 86 (W) x 86 (H) x 4 (D)

Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), MB (Metal Black), MW (Metal

White), BK (Matt Black) & PW (Polar White)

Plate Materials Decorative & Metal Black or White: Stainless Steel, Black & Polar White: Polycarbonate



SCP238BS



SCP238CH



SCP238SS



SCP238MB



SCP238MW





UK Design Registration: 3015621