

Product Code: SIN050PW

Technical Specification

Description: 13A Fused Connection Unit With Optional Flex Outlet Insert





General Information

Insert Dimensions (mm) 82.5 (W) x 82.5 (H) x 2.5 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

Style Screwless Insert Insert Colour Polar White

Compatible Cover Plate SCP150#

Materials Insert: Polycarbonate Rear Housing: Urea

Terminals: Brass Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel

Anti Microbial Certified No

Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50

Resistive Load Rating (A) 13

Fuse Fitted Rating & Type 13A (BS 1362)

Termination Type Screw

Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 2

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Switched No

Twin Earth Terminals Yes
Product Marking Fused
Flex Outlet Available Yes

Flex Outlet Location Front of Plate Flex Outlet Dimension (mm) Ø10

Minimum Back Box Depth (mm) 35

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS 1363-4 BS 1362

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.





Technical Specification



Product Code: SCP150**

Description: 13A Fused Connection Unit With Flex Outlet Cover Plate

General Information

Dimensions (mm) 86 (W) x 86 (H) x 4 (D)

Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), MB (Metal Black), MW (Metal

White), BK (Matt Black) & PW (Polar White)

Plate Materials Decorative & Metal Black or White: Stainless Steel, Black & Polar White: Polycarbonate



SCP150BS



SCP150CH



SCP150SS



SCP150MB



SCP150MW



SCP150BK

