

Technical Specification

Description: 13A 1 Gang Socket Outlet Insert





General Information

Insert Dimensions (mm) 82.5 (W) x 82.5 (H) x 2.5 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Screwless Insert

Insert Colour Black Compatible Cover Plate SCP430#

Materials Insert: Polycarbonate

Rear Housing: Urea Terminals: Brass Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel

Anti Microbial Certified

Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50

Resistive Load Rating (A) 13 Termination Type Screw

> Terminal Size (mm) Terminal Torque Value (Nm) 2 Ø5

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Switched

Twin Earth Terminals Yes

Minimum Back Box Depth (mm) 35

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS 1363-2

For cleaning / polishing of products, use only a soft, dry, clean cloth. **Additional Information**

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.







Technical Specification



Product Code: SCP430**

Description: 13A 1 Gang Socket Outlet Cover Plate

General Information

Dimensions (mm) 86 (W) x 86 (H) x 4 (D)

Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), MB (Metal Black), MW (Metal

White), BK (Matt Black) & PW (Polar White)

Plate Materials Decorative & Metal Black or White: Stainless Steel, Black & Polar White: Polycarbonate




SCP430BS



SCP430CH



SCP430SS



SCP430MB



SCP430MW



SCP430BK



SCP430PW