

Product Code: MD9102PN

Description: 10AX 2 Way Toggle Switch Module



General Information

Dimensions (mm)	25 (W) x 62 (H) x 22 (D)	
Finish	Pearl Nickel	
Materials	Body: Nylon	
	Terminal Screws: Brass	
Rated Voltage (V~) (Ue)	250	Terminals: Brass
Inductive Load Rating (AX)	10	Switch Front & Nut: Cast Zinc
Load Rating Comments	Suitable for Inductive Loads	Frequency (Hz) 50
Termination Type	Screw	
Terminal Size (mm)	4.9 x 4.1	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm²)	4 x 1.5 or 2 x 2.5	
Modular Rocker Switches	Yes	
2 Way Switch	Yes	
Minimum Back Box Depth (mm)	25 (35 Flat Plate)	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
 Suitable for Pearl Nickel, Brushed Stainless, Satin Chrome and Stainless Steel finished plates in Deco, Deco Plus, Define and Definity ranges.