



General Information

|                              |                                                                                                                                                 |                |    |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|----------------|----|
| CT202F Dimensions (mm)       | 69 (W) x 50 (D) x 23 (H)                                                                                                                        |                |    |
| CT201M Dimensions (mm)       | 54 (W) x 30 (D) x 22 (H)                                                                                                                        |                |    |
| Finish                       | Black                                                                                                                                           |                |    |
| Materials                    | Cover: Polycarbonate<br>Base & Terminal Housing: Nylon (PA66)<br>Terminals: Silver Plated Brass<br>Terminal Screws: Steel and Yellow Passivated |                |    |
| Rated Voltage (V~) (Ue)      | 250                                                                                                                                             | Frequency (Hz) | 50 |
| Resistive Load Rating (A)    | 6                                                                                                                                               |                |    |
| Cable - Assembly Rating (A)  | 6                                                                                                                                               |                |    |
| Termination Type             | Screw                                                                                                                                           |                |    |
| Cable Restraint Supplied     | Yes                                                                                                                                             |                |    |
| Ingress Protection           | IP20                                                                                                                                            |                |    |
| Operational Temperature (°C) | -5 to +40                                                                                                                                       |                |    |
| Warranty (Years)             | 10                                                                                                                                              |                |    |

Standards BS EN 61535, BS 5733, BS EN 50525-3-11

**Additional Information** Ensure that the mains supply is isolated before commencing installation. Always refer to the circuit diagram supplied with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Pre-fabricating wiring systems manufactured to BS 8488 by other manufacturers may not be compatible or safely inter-connectable with this system. Any dangerous compatibility between different manufactures installation coupler systems is not automatically prevented by compliance with IEC 61535.

