

Technical Specification

Product Code: VPSC505WH

Socket Outlet & Neons





Description: 45A Ingot 2 Gang Double Pole Switch With 13A Double Pole Switched

General Information

Plate Dimensions (mm) 146 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) $149 \text{ (W)} \times 91 \text{ (H)} \times 9 \text{ (D)}$

Plate Fixing Centres - Horizontal (mm) 120.6

Style Victorian
Finish Satin Chrome

Insert Colour White Gasket Colour White

Materials Front Plate: Stainless Steel

Neon Lens: Polycarbonate

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Gasket: Nylon

Insert & Rear Housing: Urea

Terminals: Brass

Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Anti Microbial Certified No

Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50

Resistive Load Rating (A) 45
Termination Type Screw

Terminal Size (mm) Ø6 Terminal Torque Value (Nm) 2.5

Terminal Capacity - Solid (mm²) 1 x 16

Double Pole Switch Yes
Twin Earth Terminals Yes
Neon Indicator Yes

Neon Indicator Yes Indicator Colour Red

Product Marking Cooker
Minimum Back Box Depth (mm) 35

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS 4177

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

