


Technical Specification

Product Code: FPBN505BK

Description: 45A Ingot 2 Gang Double Pole Switch With 13A Double Pole Switched

Socket Outlet & Neons





General Information

Plate Dimensions (mm) 146 (W) \times 88 (H) \times 1.3 (D) Dimensions With Gasket (mm) 146 (W) \times 88 (H) \times 3 (D)

Plate Fixing Centres - Horizontal (mm) 120.6

Style Flat Plate
Finish Black Nickel
Insert Colour Black

Gasket Colour Transparent (Neoprene)
Materials Front Plate: Stainless Steel

Neon Lens: Polycarbonate Terminals: Brass

Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Insert & Rear Housing: Urea Neon Lens: Polycarbonate

Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass

Anti Microbial Certified No

Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50

Resistive Load Rating (A) 45
Termination Type Screw

Terminal Size (mm) Ø6 Terminal Torque Value (Nm) 2.

Terminal Capacity - Solid (mm²) 1 x 16

Double Pole Switch Yes

Twin Earth Terminals Yes

Neon Indicator Yes Indicator Colour Red

Product Marking Cooker

Minimum Back Box Depth (mm) 47 Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS 4177

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



