



Product Code: PRC005      Description: T2 BC 1/2" Thread Entry Cord Grip Switched Lampholder Straight Skirt



General Information

|                                 |                                            |                                          |
|---------------------------------|--------------------------------------------|------------------------------------------|
| Dimensions (mm)                 | 44 (Dia) x 87                              |                                          |
| Finish                          | Polar White                                |                                          |
| Materials                       | Body & Skirt: Urea                         | Internal Housing: Reinforced Nylon       |
|                                 | Slide Bar: Nylon                           | Terminals: Brass                         |
|                                 | Terminal Screws: Steel & Yellow Passivated | Contacts: Silver "on-lay" Copper / Brass |
|                                 | Springs: Spring Steel                      |                                          |
| Anti Microbial Certified        | Yes                                        |                                          |
| Rated Voltage (V~) (Ue)         | 250                                        | Frequency (Hz) 50                        |
| Resistive Load Rating (A)       | 2                                          |                                          |
| Termination Type                | Screw                                      |                                          |
| Terminal Size (mm)              | Ø3.5                                       | Terminal Torque Value (Nm) 0.5           |
| Terminal Capacity - Solid (mm²) | 0.75                                       |                                          |
| Switched                        | Yes                                        |                                          |
| Double Pole Switch              | Yes                                        |                                          |
| Ingress Protection              | IP20                                       |                                          |
| Operational Temperature (°C)    | -5 to +40                                  |                                          |
| Warranty (Years)                | 10                                         |                                          |
| Standards                       | BS EN 61184                                |                                          |

**Additional Information** For cleaning / polishing of products, use only a soft, dry, clean cloth.  
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.