



Product Code: PRC038

Description: 6" T2 BC TRS Pendant Set



General Information

Dimensions (mm)	86 (Dia) x 30	
Finish	Polar White	
Materials	Cover, Body & Skirt: Urea Terminals: Brass Cable Type: 2G H05V2V2-F Springs: Spring Steel	Rear Plate: Polycarbonate Terminal Screws: Steel & Yellow Passivated Internal Housing: Reinforced Nylon
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	2	
Pre-wired Cable Specification	2G 0.75mm² H05V2V2-F	
Termination Type	Screw	
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm) 0.5
Terminal Capacity - Solid (mm²)	2 x 1.5	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	
Standards	BS EN 61184 BS 67	

Additional Information	For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Cable entry seal helps prevent moisture ingress.
------------------------	--