## essentials<sup>™</sup>

## **Technical Specification**



Product Code: CL512 Description: 2 Tier MiniGrid® Unfurnished Plate - 12 Apertures - Metal Clad



## **General Information**

**Dimensions (mm)** 148 (W) x 148 (H) x 42 (D)

MiniGrid Plate (Gang) 12

MiniGrid Single Width Module Quantity 12 (2 x 6)

MiniGrid Double Width Module Quantity 6

Style Metal Clad

Finish Metal Clad Grey

Materials Front Plate & Pattress Box:

Electrophoretically Coated Steel

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated

Anti Microbial Certified No

Yoke Required Yes (2 x GR100PW)

Supplied Back Box Depth (mm) 40

Back Box Knockouts - Total (mm)  $12 \times \emptyset 20$ ,  $1 \times 67 \times 32$ 

Back Box Knockouts - Top (mm) 3 x Ø20

Back Box Knockouts - Bottom (mm) 3 x Ø20

Back Box Earth Terminal Supplied Yes

Ingress Protection IP2

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS 5733

**Additional Information** For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Back Box Knockouts - Sides (mm) 3 x Ø20 (Each Side)

Additional Accessories CL089: 50mm Deep Back Box

CL089B: 50mm Deep Back Box Without Knockouts

