

Product Code: OA035AG

Description: 1 Gang 13A DP IP66 Weatherproof Switched Socket Unit



General Information

Dimensions (mm)	87 (W) x 158 (H) x 90 (D)		
Accessory Fixing Centres (mm)	60.3		
Finish	Anthracite Grey		
Gasket Colour	Black		
Materials	Cover, Housing & Clip: Polycarbonate Accessory Plate & Housing: Urea Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass		
Seal & Gasket:	Rubber		
Terminals:	Brass		
Contacts:	Silver "on-lay" Copper / Brass		
Earth Strap:	Mild Steel		
Anti Microbial Certified	No		
Rated Voltage (V~) (Ue)	250		
Resistive Load Rating (A)	13		
Termination Type	Screw		
Terminal Size (mm)	Ø5		
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4		
Double Pole Switch	Yes		
Back Box Knockouts - Total (mm)	7 x Ø20		
Back Box Knockouts - Top (mm)	1 x Ø20		
Back Box Knockouts - Bottom (mm)	1 x Ø20		
Ingress Protection	IP66		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	5		
Frequency (Hz)	50		
Terminal Torque Value (Nm)	2		
Back Box Knockouts - Sides (mm)	2 x Ø20		
Back Box Knockouts - Rear (mm)	1 x Ø20		
Standards	BS 1363-2 BS EN 60529		

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
All grey & white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.
All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.