



General Information

Dimensions (mm)	52 (W) x 240 (H) x 77.5 (D)		
Finish	Anthracite Grey		
Materials	Front Plate & Back Box: Electrophoretically Coated Steel Male & Female Connectors: Nylon (PA66) Terminals: Silver Plated Brass Terminal Screws: Steel and Yellow Passivated Dust Covers: Polycarbonate		
Rated Voltage (V~) (Ue)	220-240	Frequency (Hz)	50
Resistive Load Rating (A)	20		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		

Standards BS 8488, BS EN 61535, BS 5733

Additional Information Ensure that the mains supply is isolated before commencing installation. Always refer to the circuit diagram supplied with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Pre-fabricating wiring systems manufactured to BS 8488 by other manufacturers may not be compatible or safely inter-connectable with this system. Any dangerous compatibility between different manufactures installation coupler systems is not automatically prevented by compliance with IEC 61535.

Compatible Connectors Input Connector: Input Connector: Compatible With 3 and 4 Pole Connectors (Complete or Female)
Output Connectors: Compatible with 3 and 4 Pole Male Connectors

