

Product Code: VPSC770WH

Description: 13A 2 Gang Switched Socket Outlet With Single 2.1A USB Outlet



General Information

Plate Dimensions (mm)	146 (W) x 88 (H) x 8 (D)	Insert & Rocker Switch: Urea
Dimensions With Gasket (mm)	149 (W) x 91 (H) x 9 (D)	Terminals: Brass
Plate Fixing Centres - Horizontal (mm)	120.6	Contacts: Silver "on-lay" Copper / Brass
Style	Victorian	PCB: Mixed Components
Finish	Satin Chrome	Gasket: Nylon
Insert Colour	White	
Gasket Colour	White	
Materials	Front Plate: Stainless Steel Housing: Nylon Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel	
Anti Microbial Certified	No	Frequency (Hz) 50
Rated Voltage (V~) (Ue)	250	
Resistive Load Rating (A)	13	USB Charging Total Load (A) 2.1
USB Output Type	USB Type "A"	USB Standby Current (mA) 2
USB Number Of Outputs	1	
USB Charging Voltage (V DC)	5	Terminal Torque Value (Nm) 1.2
Termination Type	Screw	
Terminal Size (mm)	Ø5	
Terminal Capacity - Solid (mm ²)	3 x 2.5 or 2 x 4	
Single Pole Switched	Yes	
Twin Earth Terminals	Yes	
Product Marking	USB 5V 2.1A	
Minimum Back Box Depth (mm)	25	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	
Standards	BS 1363-2: 2016 +A1: 2018 BS EN IEC 62368-1 BS EN 62680-1-1	Warranty - Electronics (Years) 1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 The USB circuits within this socket outlet are designed to withstand insulation resistance tests at 500V.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.