






Technical Specification

Product Code: CMA612 Description: 2 Tier MiniGrid® Unfurnished Plate & Yokes - 12 Apertures



General Information

Plate Dimensions (mm) 146 (W) x 153 (H) x 9.5 (D)

MiniGrid Plate (Gang)

12 (2 x 6)

MiniGrid Single Width Module Quantity

MiniGrid Double Width Module Quantity

Style Mode

Finish

Polar White

Materials Front Plate: Urea

Terminal Housing: Urea

Terminal Screws: Steel & Yellow Passivated

Anti Microbial Certified

Termination Type Screw

Modular Rocker Switches Yes

Yoke Earth Terminal Supplied One Earth On Each Yoke

> Yoke Required No

Minimum Back Box Depth (mm)

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 20

Standards BS 5733

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of nonenveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Interchangeable with modules in the MiniGrid Range.



Earthing Yoke: Mild Steel

Terminals: Brass





