

Technical Specification

Product Code: DPAB751BK Description: 13A Ingot Double Pole Switched Fused Connection Unit





General Information

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D) Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Rounded Profile Finish Antique Brass

Insert Colour Black Gasket Colour Black

Materials Front Plate: Stainless Steel

> Switch & Fuse Drawer Cover: Stainless Steel Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Rear Housing: Urea Terminals: Brass

Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Terminal Torque Value (Nm) 2

Anti Microbial Certified

Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50

Resistive Load Rating (A) 13

Fuse Fitted Rating & Type 13A (BS 1362)

> Termination Type Screw

Terminal Size (mm) 05

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Switched

Double Pole Switch Twin Earth Terminals Yes Product Marking Fused

Minimum Back Box Depth (mm)

Ingress Protection

Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS 1363-4

BS 1362

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

