

## Technical Specification

**Product Code:** DPBN472BK

**Description:** 2 Gang MiniGrid® Unfurnished Architrave Plate - 2 Apertures



### General Information

|                                        |                                                                             |
|----------------------------------------|-----------------------------------------------------------------------------|
| Plate Dimensions (mm)                  | 35 (W) x 150 (H) x 8 (D)                                                    |
| Dimensions With Gasket (mm)            | 38 (W) x 153 (H) x 9 (D)                                                    |
| Plate Fixing Centres - Horizontal (mm) | 120.6                                                                       |
| MiniGrid Plate (Gang)                  | 2                                                                           |
| MiniGrid Single Width Module Quantity  | 2                                                                           |
| MiniGrid Double Width Module Quantity  | 0                                                                           |
| Style                                  | Rounded Profile                                                             |
| Finish                                 | Black Nickel                                                                |
| Insert Colour                          | Black                                                                       |
| Gasket Colour                          | Black                                                                       |
| Materials                              | Front Plate: Stainless Steel<br>Terminals: Brass<br>Earth Strap: Mild Steel |
| Anti Microbial Certified               | No                                                                          |
| Termination Type                       | Screw                                                                       |
| Modular Rocker Switches                | Yes                                                                         |
| Minimum Back Box Depth (mm)            | 25                                                                          |
| Ingress Protection                     | IP20                                                                        |
| Operational Temperature (°C)           | -5 to +40                                                                   |
| Warranty (Years)                       | 10                                                                          |

Insert: Urea  
Terminal Screws: Steel & Yellow Passivated

**Standards** BS 5733

### Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
Interchangeable with modules in the MiniGrid Range.

Suitable flush mounting back box WA672

