

Technical Specification

CLICK® ScolmoreGROUP

Product Code: DPBN501BK Description: 45A Ingot 1 Gang Double Pole Plate Switch With Neon





General Information

Plate Dimensions (mm) 88 (W) \times 88 (H) \times 8 (D) Dimensions With Gasket (mm) 91 (W) \times 91 (H) \times 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

Style Rounded Profile
Finish Black Nickel
Insert Colour Black

Gasket Colour Black

MaterialsFront Plate: Stainless SteelInsert & Rear Housing: UreaSwitch Cover: Stainless SteelNeon Lens: Polycarbonate

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated
Contacts: Silver "on-lay" Copper / Brass

Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Anti Microbial Certified No

Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50

Resistive Load Rating (A) 45
Termination Type Screw

Terminal Size (mm) Ø6 Terminal Torque Value (Nm) 2.5

Terminal Capacity - Solid (mm²) 1 x 16

Double Pole Switch Yes

Twin Earth Terminals Yes

Neon Indicator Yes Indicator Colour Red

Product Marking On & Off
Minimum Back Box Depth (mm) 35

Ingress Protection IP20
Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS EN 60669-1

Additional Information For cleaning / pol

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

