

Technical Specification



Product Code: DPBN523BK Description: 20A Ingot Double Pole Plate Switch With Optional Flex Outlet With Neon





General Information

 $\begin{array}{ccc} \textbf{Plate Dimensions (mm)} & 88 \text{ (W)} \times 88 \text{ (H)} \times 8 \text{ (D)} \\ \textbf{Dimensions With Gasket (mm)} & 91 \text{ (W)} \times 91 \text{ (H)} \times 9 \text{ (D)} \\ \end{array}$

Plate Fixing Centres - Horizontal (mm) 60.3

Style Rounded Profile
Finish Black Nickel
Insert Colour Black

Gasket Colour Black

MaterialsFront Plate: Stainless SteelInsert & Housing: UreaSwitch Cover: Stainless SteelNeon Lens: Polycarbonate

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated
Contacts: Silver "on-lay" Copper / Brass

Internal Busbars: Formed Pressed Brass

Contacts, onver on-lay copper,

Earth Strap: Mild Steel

Anti Microbial Certified No

Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50

Resistive Load Rating (A) 20 Termination Type Screw

Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 1.8

Terminal Capacity - Solid (mm²) 3 x 2.5 Double Pole Switch Yes

Twin Earth Terminals Yes

Neon Indicator Yes Indicator Colour Red

Flex Outlet Available Yes

Flex Outlet Location Front of Plate Flex Outlet Dimension (mm) Ø10

Minimum Back Box Depth (mm) 25

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS EN 60669-1

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



E: sales@scolmore.com | W: scolmore.com