


**Product Code:** DPSB504BK

**Description:** 45A Ingot 2 Gang Double Pole Switch With 13A Double Pole Switched Socket Outlet



## General Information

|                                        |                                                                                                                         |                                                                                                                     |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Plate Dimensions (mm)                  | 146 (W) x 88 (H) x 8 (D)                                                                                                |                                                                                                                     |
| Dimensions With Gasket (mm)            | 149 (W) x 91 (H) x 9 (D)                                                                                                |                                                                                                                     |
| Plate Fixing Centres - Horizontal (mm) | 120.6                                                                                                                   |                                                                                                                     |
| Style                                  | Rounded Profile                                                                                                         |                                                                                                                     |
| Finish                                 | Satin Brass                                                                                                             |                                                                                                                     |
| Insert Colour                          | Black                                                                                                                   |                                                                                                                     |
| Gasket Colour                          | Black                                                                                                                   |                                                                                                                     |
| Materials                              | Front Plate: Stainless Steel<br>Terminals: Brass<br>Contacts: Silver "on-lay" Copper / Brass<br>Earth Strap: Mild Steel | Insert & Rear Housing: Urea<br>Terminal Screws: Steel & Yellow Passivated<br>Internal Busbars: Formed Pressed Brass |
| Anti Microbial Certified               | No                                                                                                                      |                                                                                                                     |
| Rated Voltage (V~) (Ue)                | 250                                                                                                                     | Frequency (Hz) 50                                                                                                   |
| Resistive Load Rating (A)              | 45                                                                                                                      |                                                                                                                     |
| Termination Type                       | Screw                                                                                                                   |                                                                                                                     |
| Terminal Size (mm)                     | Ø6                                                                                                                      | Terminal Torque Value (Nm) 2.5                                                                                      |
| Terminal Capacity - Solid (mm²)        | 1 x 16                                                                                                                  |                                                                                                                     |
| Double Pole Switch                     | Yes                                                                                                                     |                                                                                                                     |
| Twin Earth Terminals                   | Yes                                                                                                                     |                                                                                                                     |
| Product Marking                        | Cooker                                                                                                                  |                                                                                                                     |
| Minimum Back Box Depth (mm)            | 35                                                                                                                      |                                                                                                                     |
| Ingress Protection                     | IP20                                                                                                                    |                                                                                                                     |
| Operational Temperature (°C)           | -5 to +40                                                                                                               |                                                                                                                     |
| Warranty (Years)                       | 10                                                                                                                      |                                                                                                                     |

**Standards** BS 4177

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.