

## Technical Specification

Product Code: DPSB723WH

Description: 20A Ingot Double Pole Plate Switch With Neon



### General Information

|  |  |  |
|--|--|--|
| Plate Dimensions (mm)                        | 88 (W) x 88 (H) x 8 (D)  |  |
| Dimensions With Gasket (mm)                  | 91 (W) x 91 (H) x 9 (D)  |  |
| Plate Fixing Centres - Horizontal (mm)       | 60.3   |  |
| Style  | Rounded Profile  |  |
| Finish                                       | Satin Brass  |  |
| Insert Colour                                | White  |  |
| Gasket Colour                                | White  |  |
| Materials                                    | Front Plate: Stainless Steel<br>Switch Cover: Stainless Steel<br>Terminals: Brass<br>Contacts: Silver "on-lay" Copper / Brass<br>Earth Strap: Mild Steel | Insert & Housing: Urea<br>Neon Lens: Polycarbonate<br>Terminal Screws: Steel & Yellow Passivated<br>Internal Busbars: Formed Pressed Brass |
| Anti Microbial Certified                     | No   |  |
| Rated Voltage (V~) (Ue)                      | 250  | Frequency (Hz) 50  |
| Resistive Load Rating (A)                    | 20   |  |
| Termination Type                             | Screw  |  |
| Terminal Size (mm)                           | Ø5   | Terminal Torque Value (Nm) 1.8   |
| Terminal Capacity - Solid (mm <sup>2</sup> ) | 3 x 2.5  |  |
| Double Pole Switch                           | Yes  |  |
| Twin Earth Terminals                         | Yes  |  |
| Neon Indicator                               | Yes  | Indicator Colour Red   |
| Minimum Back Box Depth (mm)                  | 25   |  |
| Ingress Protection                           | IP20   |  |
| Operational Temperature (°C)                 | -5 to +40  |  |
| Warranty (Years)                             | 10   |  |

**Standards** BS EN 60669-1

### Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.