

Product Code: DPSC039BK

Description: 2A Round Pin Socket Outlet



General Information

| | | |
|--|--|--|
| Plate Dimensions (mm) | 88 (W) x 88 (H) x 8 (D) | |
| Dimensions With Gasket (mm) | 91 (W) x 91 (H) x 9 (D) | |
| Plate Fixing Centres - Horizontal (mm) | 60.3 | |
| Style | Rounded Profile | |
| Finish | Satin Chrome | |
| Insert Colour | Black | |
| Gasket Colour | Black | |
| Materials | Front Plate: Stainless Steel Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated Earth Strap: Mild Steel | Insert: Urea Terminals: Brass Internal Busbars: Formed Pressed Brass |
| Anti Microbial Certified | No | |
| Rated Voltage (V~) (Ue) | 250 | Frequency (Hz) 50 |
| Resistive Load Rating (A) | 2 | |
| Termination Type | Screw | |
| Terminal Size (mm) | Ø5 | Terminal Torque Value (Nm) 0.5 |
| Terminal Capacity - Solid (mm²) | 3 x 1.5 | |
| Switched | No | |
| Twin Earth Terminals | No | |
| Minimum Back Box Depth (mm) | 25 | |
| Ingress Protection | IP20 | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 10 | |
| Standards | BS 546 | |

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.