Technical Specification

Product Code: DPSC502BK **Description:** 45A Ingot 2 Gang (Vertical) Double Pole Plate Switch

General Information

Plate Dimensions (mm)	88 (W) x 146 (H) x 8 (D)
Dimensions With Gasket (mm)	91 (W) x 149 (H) x 9 (D)
Plate Fixing Centres - Horizontal (mm)	120.6
Style	Rounded Profile
Finish	Satin Chrome
Insert Colour	Black
Gasket Colour	Black
Materials	Front Plate: Stainless Steel Switch Cover: Stainless Steel Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Insert & Rear Housing: Urea Terminals: Brass Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel
Anti Microbial Certified	No
Rated Voltage (V~) (Ue)	250
Frequency (Hz)	50
Resistive Load Rating (A)	45
Termination Type	Screw
Terminal Size (mm)	Ø6
Terminal Torque Value (Nm)	2.5
Terminal Capacity - Solid (mm²)	1 x 16
Double Pole Switch	Yes
Twin Earth Terminals	Yes
Product Marking	On & Off
Minimum Back Box Depth (mm)	35
Ingress Protection	IP20
Operational Temperature (°C)	-5 to +40
Warranty (Years)	10

Standards

BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

Errors & Omissions excluded.
Specification is subject to change without notice.